

# **S-Series 19" Swing Frame Racks**

Our "S-Series" range of Hypertec 19" Swing Frame Racks provides all the unique features you have come to enjoy on our "S-Series" wall mount range, with added swing-away feature. When additional uncompromising access is required, the rack can be unlocked and swung away from the wall allowing full access to the rear of your equipment for installation and/or regular servicing.

The racks are great for underneath stairwells or tight corners. Sturdy welded frame manufactured to precise dimensions from SPCC high quality cold rolled steel with a thickness of 1.5mm for the rails, 1.2mm for the frame and 1.0mm side panels, making Hypertec racks very rigid under load conditions. Hypertec Wall Mount and Swing Frame Racks are design to carry your valuable equipment up to a 60kg weight load when installed on suitable walls and in accordance with the manufacturer's instructions.

	DIMENSIONS (mm)					INCLUDED ACCESSORIES				
PART NO.	RU	Weight (kg)	Width	Depth	Height	Fixed Shelves	Fans	6 Way PDU (10A)	Cage Nuts	
HRSF6RU-S	6	17	600	600	370	1	0	1	40	
HRSF9RU-S	9	21	600	600	500	1	0	1	40	
HRSF12RU-S	12	23	600	600	635	1	0	1	40	
HRSF18RU-S	18	31	600	600	900	1	0	1	40	







## CONSTRUCTION

- Sturdy welded frame made from high quality cold rolled steel
- Rails 1.5mm, Frame and Door 1.2mm, Side Panels 1mm
- · Max load 60kg
- · Colour Black RAL 9005

#### **SWING FRAME DESIGN**

- · Easy to access installed equipment
- Locator pins help align the door to the frame when closing
- Keyed lock prevents unauthorised persons opening the swing frame



## **GLASS DOOR**

- Fully tempered glass 4mm
- · Clear view of inside cabinet
- · Earth lead connected to door
- Quick release hinge
- Dorrs can be changed to left or right opening via quick release hinges

#### SIDE PANELS

- Removable side panels
- Keyed cam locks included

#### MOUNTING

- Features 4x keyhole shaped holes to easily mount onto the
- Before mounting to a wall, ensure that the wall structure has enough strength to support the rack and its load

## RAIL

- Max load 60kg
- RU marking printed on the front and rear rails for easy placement of components
- Easy to adjust rails
- Numerous accessories available for rail mounting

#### **CABLE ACCESS**

- Rear cable access via 2x knockouts, allowing cable to enter rear of rack out of sight
- Generous cable access on top and bottom via removable
- 2x cable access on top. 2x cable access on bottom.

#### **AIR FLOW**

- Fan cutouts on top for mounting up to 2x 120mm fans
- · Covered fan cutouts on top prevent dust entering if fans are not installed

#### **PDU**

- · 6-way 10A horizontal rail mounted
- Australian 3 pin plug and sockets
- PDU range available as optional extra

## CABLE MANAGEMENT

- 70mm between front door and rail for cable management
- Horizontal cable management accessories available


#### **SHELF ACCESSORIES**

- Cantilever trays
- Fixed shelves



# **Accessories: Shelves**

The Hypretec range of shelving accessories for our 19" Rack Enclosures are designed to offer solutions for most requirements and cover many shelf types for floor mounted cabinets of various depths. Some items are suitable for wall mount & swing frame racks.



		DESCRIPTION				WIDTL	DIEDACE	MOUNTING		
NO.	NO.	DESCRIPTION	TYPE	DEPTH	DEPTH	WIDTH	RU SPACE	MOUNTING	KG	LOAD KG
1	HRCS300-S	Hypertec Cantilever Shelf 483 x 300 x 43	ALL	ALL	300	483	1	RU Rail	2.5	20
'	HRCS350-S	Hypertec Cantilever Shelf 483 x 350 x 43	ALL	ALL	350	483	1	RU Rail	3	20
	HRCS400-S	Hypertec Cantilever Shelf 483 x 350 x 43	ALL	600 to 1000	400	483	1	RU Rail	3.5	20
2	HRCS300	Cantilever Shelf 19" RM 300mm Black	ALL	ALL	300	485	2	RU Rail	2.5	30
2	HRCS400	Cantilever Shelf 19" RM 400mm Black	ALL	600 to 1000	400	485	2	RU Rail	3.2	30
3	HRFT320-S	Hypertec Fixed Shelf 480 x 270 x 48	SF	600	320	480	0	Side Rail	1.8	90

**SUITS RACK** 

KEY	WM	Wall mount
	SF	Swing Frame
	FM	Floor Mount