

- High precision cleaving for ribbon fiber cable as well as 160µm to 900µm, 2mm~3mm and drop cable with universal holder
- Durable blade lifetime over 48,000 fiber cleaves



# High Precision Single & Ribbon Fiber Cleaver

V7

Compatible with all VIEW series fusion splicers Available for single and ribbon cleaving up to 12 fibers Easy and simple 2 step operation Automatic fiber shard collector (optional) 5

# Description

V7 High Precision Cleaver is an instrument for high precision fiber cutting. V7 can be installed with a variety of holders for ribbon cable up to 12 fibers as well as universal holder which is applicable to 160µm to 900µm, 2mm~3mm and drop cable. Work efficiency can be maximized with easy and simple 2 step operations. V7+as an optional model has an automatic collector for fiber shards and off cuts. The blade provides over 48,000 fiber cleaves by easy and simple blade position selection. Helped by unmatched functionalities, users can achieve the most accurate cleaving and ideally prepare their fusion splicing.

## Universal Single Holder Replaceable Ribbon Holder

#### Option V7+ (Equipped with automatic shard collector)



Specifications	
Туре	Single fiber and ribbon fiber
Cladding Diameter	125µm
Applicable Fiber Cable	Single Fiber : 160µm to 900µm, 2mm~3mm and drop cable Ribbon Fiber : 2 to 12 ribbon fiber cable
Cleaved Length	Single Fiber : 5mm~24mm (Coating diameter ≤ 250µm) 10mm~20mm (Coating diameter >250µm) Ribbon (Multi) Fiber : 10mm~20mm
Typical Cleaved Angle	Less than 0.5 Degrees
Typical Blade Life Span	Total 48,000 fiber cleaves (1,000 fiber for 1 step * total 16 points * 3 heights)
Operation Steps	2 Steps
Reclaim Function	Blade pushback
Holder	Single: Universal holder / Ribbon: Replaceable holder

## Size and Weight



62mr

## Package



The information on this catalog is subject to change without prior notice.

In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where shown, may not be to scale. Dimensions are metric and size maybe approximate. Where possible data sheets including MSDS are made available on our website and apps. All products should be installed and used in accordance to manufacturer's instruction provided. Warning: products may be subject of registered designs and patents. Refer to our website or apps for terms and conditions on warranty.

(82 mm) Weight 0.85 pounds (387 grams)

# mssdatasolutions.com.au