

CURRENT CLAMP 600A AC



Part No. T9001

This 600AAC clamp is a new generation of clamp meter with some exceptional features such as NCV (non-contact voltage detection). Compact, with a double moulded housing, this meter is attractive, reliable and feature filled.

- 3 3/4 Digit 4000 count LCD
- Data hold/relative
- Frequency
- Duty cycle
- Auto-power 'off'
- Diode test
- Double moulded housing
- EF or NCV test 100 to 600V

EA QTY 1

Compliance and Safety	EN61010 CAT IV 600V pollution degree 2, CE
Contents	The T9001 comes in a gift box with test leads and operating manual.
Dimensions	L233 x W80 x T43 mm
Batteries	9V 6F22 giving ± 200hrs
Weight	344g with the battery
Replacement Test Leads	AL04

Feature	Range	Resolution	Accuracy
DC Voltage	400m/4/40/400/600 V	100V	± 0.5% ± 1
AC Voltage	400m/4/40/400/600 V	1mV (0.1mV on 400mV range)	± 1% ± 4
AC Current	40/400/600 A	0.01 A	± 3.5% ± 5
Resistance	400/4k/40k/400k/4M/40MΩ	0.1Ω	± 3% ± 4
Capacitance	40n/400nF/4/40/100µF	0.1n F	± 3% ± 10
Frequency	5/50/5k/50k/500k5MHz	0.01 Hz	± 0.1% ± 3
Duty Cycle	2Hz to 10Hz; 10% to 90%	0.1%	± 2% ± 5
Jaw Size	42mm		

In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where shown, may not be to scale. Dimensions are metric and size maybe approximate. Where possible data sheets including MSDS are made available on our website and apps. All products should be installed and used in accordance to manufacturer's instruction provided. Warning: products may be subject of registered designs and patents. Refer to our website or apps for terms and conditions on warranty.